

No.	Size	HT Pattern	Rim	Ply Rating	LI/SS	Second LI/SS	Max. Load (Single-KG)	Max. Pressure (Single-KPa)	Max. Load (Dual-KG)	Max. Pressure (Dual-KPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	DOT	M+S	3PMSF	EU-RR (Level)	EU-WG (Level)	EU-N (Level)	EU-N (dB)	HL
1	11R22.5	HIGHWAY D12	8.25	14	144/142L	-	2800	720	2650	720	1065	279	22	YES	-	-	-	-	-	-	-
2	11R22.5	HIGHWAY D12	8.25	16	146/143L	-	3000	830	2725	830	1065	279	22	YES	-	-	-	-	-	-	-
3	11R22.5	HIGHWAY D16	8.25	14	144/142M	-	2800	720	2650	720	1065	279	22.0	YES	-	-	-	-	-	-	-
4	11R22.5	HIGHWAY D16	8.25	16	146/143M	-	3000	830	2725	830	1065	279	22.0	YES	-	-	-	-	-	-	-
5	11R22.5	HIGHWAY S12	8.25	14	144/142M	-	2800	720	2650	720	1054	279	14.5	YES	-	-	-	-	-	-	-
6	11R22.5	HIGHWAY S12	8.25	16	146/143M	-	3000	830	2725	830	1054	279	14.5	YES	-	-	-	-	-	-	-
7	11R22.5	MINE D11	8.25	16	146/143K	-	3000	830	2725	830	1065	279	23.0	YES	-	-	-	-	-	-	-
8	11R22.5	MIXED G11	8.25	14	144/142K	-	2800	720	2650	720	1054	279	15.0	YES	-	-	-	-	-	-	-
9	11R22.5	MIXED G11	8.25	16	146/143K	-	3000	830	2725	830	1054	279	15.0	YES	-	-	-	-	-	-	-
10	11R22.5	MIXED G11	8.25	16	148/145K	-	3150	850	2900	850	1050	279	16.5	YES	YES	YES	D	B	2	73	-
11	11R22.5	MIXED G11	8.25	16	148/145K	-	3150	850	2900	850	1054	279	15.0	YES	-	-	-	-	-	-	-
12	11R22.5	REGIONAL D15	8.25	14	144/142L	-	2800	720	2650	720	1059	279	20.5	YES	-	-	-	-	-	-	-
13	11R22.5	REGIONAL D15	8.25	16	146/143L	-	3000	830	2725	830	1059	279	20.5	YES	-	-	-	-	-	-	-
14	11R22.5	REGIONAL S12	8.25	14	144/142M	-	2800	720	2650	720	1054	279	14.5	YES	-	-	-	-	-	-	-
15	11R22.5	REGIONAL S12	8.25	16	146/143M	-	3000	830	2725	830	1054	279	14.5	YES	-	-	-	-	-	-	-
16	11R22.5	REGIONAL T12	8.25	14	144/142M	-	2800	720	2650	720	1050	279	10.75	YES	-	-	-	-	-	-	-
17	11R22.5	REGIONAL T12	8.25	16	146/143M	-	3000	830	2725	830	1050	279	10.75	YES	-	-	-	-	-	-	-
18	11R22.5	URBAN G12	8.25	16	146/143M	-	3000	830	2725	830	1054	279	16.0	YES	-	-	-	-	-	-	-
19	11R22.5	URBAN G15	8.25	16	146/143F	-	3000	830	2725	830	1054	279	20.0	YES	-	-	-	-	-	-	-
20	11R22.5	WINTER D12	8.25	16	146/143L	-	3000	830	2725	830	1065	279	21.5	YES	-	-	-	-	-	-	-
21	11R22.5	WINTER D15	8.25	16	146/143M	-	3000	830	2725	830	1054	279	20.0	YES	-	-	-	-	-	-	-
22	11R22.5	WINTER G11	8.25	16	146/143M	-	3000	830	2725	830	1054	279	15.0	YES	-	-	-	-	-	-	-
23	11R24.5	HIGHWAY D12	8.25	14	146/143L	-	3000	720	2725	720	1116	279	22	YES	-	-	-	-	-	-	-
24	11R24.5	HIGHWAY D12	8.25	16	149/146L	-	3250	830	3000	830	1116	279	22	YES	-	-	-	-	-	-	-
25	11R24.5	HIGHWAY D16	8.25	14	146/143M	-	3000	720	2725	720	1116	279	22.0	YES	-	-	-	-	-	-	-
26	11R24.5	HIGHWAY D16	8.25	16	149/146M	-	3250	830	3000	830	1116	279	22.0	YES	-	-	-	-	-	-	-
27	11R24.5	HIGHWAY S12	8.25	14	146/143M	-	3000	720	2725	720	1104	279	14.5	YES	-	-	-	-	-	-	-
28	11R24.5	HIGHWAY S12	8.25	16	149/146M	-	3250	830	3000	830	1104	279	14.5	YES	-	-	-	-	-	-	-
29	11R24.5	MINE D11	8.25	16	149/146G	-	3250	830	3000	830	1116	279	25.0	YES	-	-	-	-	-	-	-
30	11R24.5	MIXED G11	8.25	16	149/146K	-	3250	830	3000	830	1104	279	15.5	YES	-	-	-	-	-	-	-
31	11R24.5	REGIONAL D15	8.25	14	146/143L	-	3000	720	2725	720	1110	279	20.5	YES	-	-	-	-	-	-	-
32	11R24.5	REGIONAL D15	8.25	16	149/146L	-	3250	830	3000	830	1110	279	20.5	YES	-	-	-	-	-	-	-
33	11R24.5	REGIONAL S12	8.25	14	146/143M	-	3000	720	2725	720	1104	279	14.5	YES	-	-	-	-	-	-	-
34	11R24.5	REGIONAL S12	8.25	16	149/146M	-	3250	830	3000	830	1104	279	14.5	YES	-	-	-	-	-	-	-
35	11R24.5	REGIONAL T12	8.25	14	146/143M	-	3000	720	2725	720	1100	279	10.75	YES	-	-	-	-	-	-	-
36	11R24.5	REGIONAL T12	8.25	16	149/146M	-	3250	830	3000	830	1100	279	10.75	YES	-	-	-	-	-	-	-
37	11R24.5	WINTER D12	8.25	16	149/146L	-	3250	830	3000	830	1116	279	21.5	YES	-	-	-	-	-	-	-
38	11R24.5	WINTER G11	8.25	16	149/146M	-	3250	830	3000	830	1104	279	15.0	YES	-	-	-	-	-	-	-
39	12.00R20	MIXED G11	8.50	18	154/151K	-	3750	830	3450	830	1125	315	17.0	YES	YES	YES	D	B	2	73	-
40	12.00R24	MIXED G11	8.50	18	156/153K	-	4000	775	3650	775	1226	313	17.0	YES	YES	YES	D	B	2	73	-

No.	Size	HT Pattern	Rim	Ply Rating	LI/SS	Second LI/SS	Max. Load (Single-KG)	Max. Pressure (Single-KPa)	Max. Load (Dual-KG)	Max. Pressure (Dual-KPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	DOT	M+S	3PMSF	EU-RR (Level)	EU-WG (Level)	EU-N (Level)	EU-N (dB)	HL
41	12.00R24	MIXED G11	8.50	20	160/156K	-	4500	850	4000	850	1226	313	17.0	YES	YES	YES	D	B	2	73	-
42	12R22.5	MIXED G11	9.00	16	150/147K	-	3350	830	3075	830	1085	300	17.0	YES	-	-	-	-	-	-	-
43	12R22.5	MIXED G11	9.00	16	152/148K	-	3550	850	3150	850	1084	300	17.0	YES	YES	YES	D	B	2	73	-
44	12R22.5	MIXED G11	9.00	18	152/149K	-	3550	930	3250	930	1085	300	17.0	YES	-	-	-	-	-	-	-
45	12R22.5	URBAN G12	9.00	16	150/147L	-	3350	830	3075	830	1085	300	17.0	YES	-	-	-	-	-	-	-
46	12R22.5	URBAN G12	9.00	18	152/149L	-	3550	930	3250	930	1085	300	17.0	YES	-	-	-	-	-	-	-
47	13R22.5	MIXED D11	9.75	18	156/150K	-	4000	875	3350	875	1124	320	21.0	YES	YES	YES	D	B	2	73	-
48	13R22.5	MIXED G15	9.75	18	156/150K	-	4000	875	3350	875	1124	320	19.0	YES	YES	YES	D	B	2	73	-
49	13R22.5	MIXED G15	9.75	20	158/156K	-	4250	900	4000	900	1124	320	19.0	YES	YES	YES	D	B	2	73	-
50	205/65R17.5	REGIONAL T11	6.00	16	129/127J	132/132G	1850	900	1750	900	711	204	12.5	YES	YES	-	D	B	2	72	-
51	215/75R17.5	REGIONAL D12	6.00	14	126/124M	-	1700	700	1600	700	767	211	14.0	YES	YES	YES	D	C	2	73	-
52	215/75R17.5	REGIONAL G11	6.00	14	126/124L/M	-	1700	700	1600	700	767	211	12.5	YES	YES	YES	E	B	2	72	-
53	215/75R17.5	REGIONAL G11	6.00	16	135/133J	-	2180	850	2060	850	767	211	12.5	YES	-	-	-	-	-	-	-
54	215/75R17.5	REGIONAL G11	6.00	16	135/133J/L	-	2180	850	2060	850	767	211	12.5	YES	YES	YES	E	B	2	72	-
55	215/75R17.5	REGIONAL S15	6.00	14	126/124M	-	1700	700	1600	700	767	211	12.5	YES	YES	YES	D	B	2	73	-
56	215/75R17.5	REGIONAL S15	6.00	16	135/133J	-	2180	850	2060	850	767	211	12.5	YES	YES	YES	D	B	2	73	-
57	215/75R17.5	REGIONAL T11	6.00	16	135/133J	-	2180	850	2060	850	767	211	12.5	YES	YES	-	D	B	2	72	-
58	225/75R17.5	REGIONAL D12	6.75	12	126/125M	-	1700	675	1650	675	783	226	14.5	YES	YES	YES	D	C	2	73	-
59	225/75R17.5	REGIONAL D12	6.75	14	129/127M	-	1850	725	1750	725	783	226	14.5	YES	YES	YES	D	C	2	73	-
60	225/75R17.5	REGIONAL S15	6.75	12	126/125M	-	1700	675	1650	675	783	226	12.5	YES	YES	YES	D	B	2	73	-
61	225/75R17.5	REGIONAL S15	6.75	14	129/127M	-	1850	725	1750	725	783	226	12.5	YES	YES	YES	D	B	2	73	-
62	235/75R17.5	REGIONAL D12	6.75	14	132/130M	-	2000	775	1900	775	797	233	14.5	YES	YES	YES	D	C	2	73	-
63	235/75R17.5	REGIONAL S15	6.75	14	132/130M	-	2000	775	1900	775	797	233	12.5	YES	YES	YES	D	B	2	73	-
64	235/75R17.5	REGIONAL S15	6.75	16	141/140J	-	2575	850	2500	850	797	233	12.5	YES	YES	YES	D	B	2	73	-
65	235/75R17.5	REGIONAL S15	6.75	18	143/141J	-	2725	875	2575	875	797	233	12.5	YES	YES	YES	D	B	2	73	-
66	235/75R17.5	REGIONAL T11	6.75	16	141/140J	-	2575	850	2500	850	797	233	12.5	YES	YES	-	D	B	2	72	-
67	235/75R17.5	REGIONAL T11	6.75	18	143/141J	-	2725	875	2575	875	797	233	12.5	YES	YES	-	D	B	2	72	-
68	245/70R17.5	REGIONAL D12	7.50	14	134/132M	-	2120	775	2000	775	789	248	14.5	YES	YES	YES	D	C	2	73	-
69	245/70R17.5	REGIONAL D12	7.50	16	136/134M	-	2240	850	2120	850	789	248	14.5	YES	YES	YES	D	C	2	73	-
70	245/70R17.5	REGIONAL S15	7.50	14	134/132M	-	2120	775	2000	775	789	248	12.5	YES	YES	YES	D	B	2	73	-
71	245/70R17.5	REGIONAL S15	7.50	16	136/134M	-	2240	850	2120	850	789	248	12.5	YES	YES	YES	D	B	2	73	-
72	245/70R17.5	REGIONAL S15	7.50	18	143/141J	-	2725	875	2575	875	789	248	12.5	YES	YES	YES	D	B	2	73	-
73	245/70R17.5	REGIONAL T11	7.50	18	143/141J	-	2725	875	2575	875	789	248	12.5	YES	YES	-	D	B	2	72	-
74	245/70R19.5	REGIONAL D12	7.50	14	133/131M	-	2060	750	1950	750	839	248	14.5	YES	YES	YES	D	C	2	73	-
75	245/70R19.5	REGIONAL D12	7.50	16	136/134M	-	2240	825	2120	825	839	248	14.5	YES	YES	YES	D	C	2	73	-
76	245/70R19.5	REGIONAL S15	7.50	12	129/127M	-	1850	660	1750	660	839	248	12.5	YES	YES	YES	D	B	2	73	-
77	245/70R19.5	REGIONAL S15	7.50	14	133/131M	-	2060	760	1950	760	839	248	12.5	YES	YES	YES	D	B	2	73	-
78	245/70R19.5	REGIONAL S15	7.50	14	133/131M	-	2060	750	1950	750	839	248	12.5	YES	YES	YES	D	B	2	73	-
79	245/70R19.5	REGIONAL S15	7.50	16	136/134M	-	2240	825	2120	825	839	248	12.5	YES	YES	YES	D	B	2	73	-
80	255/70R22.5	MIXED G11	7.50	16	140/137M	-	2500	830	2300	830	930	255	12.7	YES	-	-	-	-	-	-	-

No.	Size	HT Pattern	Rim	Ply Rating	L/SS	Second L/SS	Max. Load (Single-KG)	Max. Pressure (Single-KPa)	Max. Load (Dual-KG)	Max. Pressure (Dual-KPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	DOT	M+S	3PMSF	EU-RR (Level)	EU-WG (Level)	EU-N (Level)	EU-N (dB)	HL
81	255/70R22.5	REGIONAL T12	7.50	16	140/137M	-	2500	830	2300	830	930	255	10.75	YES	-	-	-	-	-	-	-
82	265/70R19.5	REGIONAL D12	7.50	14	136/134M	-	2240	725	2120	725	867	262	15.5	YES	YES	YES	D	C	2	73	-
83	265/70R19.5	REGIONAL D12	7.50	16	140/138M	-	2500	775	2360	775	867	262	15.5	YES	YES	YES	D	C	2	73	-
84	265/70R19.5	REGIONAL S15	7.50	14	136/134M	-	2240	725	2120	725	867	262	13.5	YES	YES	YES	D	B	2	73	-
85	265/70R19.5	REGIONAL S15	7.50	16	140/138M	-	2500	775	2360	775	867	262	13.5	YES	YES	YES	D	B	2	73	-
86	265/70R19.5	REGIONAL S15	7.50	18	143/141J	-	2725	850	2575	850	867	262	13.5	YES	YES	YES	D	B	2	73	-
87	275/70R22.5	URBAN G11	8.25	16	148/145J	-	3150	900	2900	900	958	276	21.0	NO	-	-	D	B	2	73	-
88	275/70R22.5	URBAN G12	8.25	16	148/145M	-	3150	900	2900	900	958	276	16.0	YES	-	-	-	-	-	-	-
89	275/70R22.5	URBAN G15	8.25	16	148/145J	152/148E	3150	900	2900	900	958	276	19.5	YES	-	-	-	-	-	-	-
90	275/70R22.5	WINTER G11	8.25	16	148/145M	-	3150	900	2900	900	958	276	15.0	YES	-	-	-	-	-	-	-
91	285/70R19.5	REGIONAL D12	8.25	18	146/144M	-	3000	900	2800	900	895	283	16.0	YES	YES	YES	D	C	2	73	-
92	285/70R19.5	REGIONAL S15	8.25	18	146/144M	-	3000	900	2800	900	895	283	13.5	YES	YES	YES	D	B	2	73	-
93	285/70R19.5	REGIONAL S15	8.25	18	150/148J	-	3350	900	3150	900	895	283	13.5	YES	YES	YES	D	B	2	73	-
94	285/75R24.5	HIGHWAY D12	8.25	14	144/141L	-	2800	760	2575	760	1066	283	22	YES	-	-	-	-	-	-	-
95	285/75R24.5	HIGHWAY D12	8.25	16	147/144L	-	3075	830	2800	830	1066	283	22	YES	-	-	-	-	-	-	-
96	285/75R24.5	HIGHWAY D16	8.25	14	144/141M	-	2800	760	2575	760	1066	283	22.0	YES	-	-	-	-	-	-	-
97	285/75R24.5	HIGHWAY D16	8.25	16	147/144M	-	3075	830	2800	830	1066	283	22.0	YES	-	-	-	-	-	-	-
98	285/75R24.5	HIGHWAY S12	8.25	14	144/141M	-	2800	760	2575	760	1050	283	14.5	YES	-	-	-	-	-	-	-
99	285/75R24.5	HIGHWAY S12	8.25	16	147/144M	-	3075	830	2800	830	1050	283	14.5	YES	-	-	-	-	-	-	-
100	285/75R24.5	REGIONAL D15	8.25	14	144/141M	-	2800	760	2575	760	1056	283	20.5	YES	-	-	-	-	-	-	-
101	285/75R24.5	REGIONAL D15	8.25	16	147/144M	-	3075	830	2800	830	1056	283	20.5	YES	-	-	-	-	-	-	-
102	285/75R24.5	REGIONAL S12	8.25	14	144/141M	-	2800	760	2575	760	1050	283	14.5	YES	-	-	-	-	-	-	-
103	285/75R24.5	REGIONAL S12	8.25	16	147/144M	-	3075	830	2800	830	1050	283	14.5	YES	-	-	-	-	-	-	-
104	285/75R24.5	REGIONAL T12	8.25	14	144/141M	-	2800	760	2575	760	1050	283	10.75	YES	-	-	-	-	-	-	-
105	285/75R24.5	REGIONAL T12	8.25	16	147/144M	-	3075	830	2800	830	1050	283	10.75	YES	-	-	-	-	-	-	-
106	295/60R22.5	HIGHWAY D11	9.00	16	150/147L	-	3350	900	3075	900	926	292	16.0	YES	YES	YES	D	C	2	75	-
107	295/60R22.5	HIGHWAY S11	9.00	16	150/147L	-	3350	900	3075	900	926	292	13.0	YES	YES	YES	D	C	2	73	-
108	295/60R22.5	REGIONAL D11	9.00	16	150/147L	-	3350	900	3075	900	926	292	18.0	YES	YES	YES	E	B	2	75	-
109	295/60R22.5	REGIONAL S11	9.00	16	150/147L	-	3350	900	3075	900	926	292	14.0	YES	YES	YES	C	C	2	73	-
110	295/75R22.5	HIGHWAY D12	9.00	14	144/141L	-	2800	760	2575	760	1026	298	22	YES	-	-	-	-	-	-	-
111	295/75R22.5	HIGHWAY D12	9.00	16	146/143L	-	3000	830	2725	830	1026	298	22	YES	-	-	-	-	-	-	-
112	295/75R22.5	HIGHWAY D16	9.00	14	144/141M	-	2800	760	2575	760	1026	298	22.0	YES	-	-	-	-	-	-	-
113	295/75R22.5	HIGHWAY D16	9.00	16	146/143M	-	3000	830	2725	830	1026	298	22.0	YES	-	-	-	-	-	-	-
114	295/75R22.5	HIGHWAY S12	9.00	14	144/141M	-	2800	760	2575	760	1014	298	14.5	YES	-	-	-	-	-	-	-
115	295/75R22.5	HIGHWAY S12	9.00	16	146/143M	-	3000	830	2725	830	1014	298	14.5	YES	-	-	-	-	-	-	-
116	295/75R22.5	REGIONAL D15	9.00	14	144/141M	-	2800	760	2575	760	1020	298	20.5	YES	-	-	-	-	-	-	-
117	295/75R22.5	REGIONAL D15	9.00	16	146/143M	-	3000	830	2725	830	1020	298	20.5	YES	-	-	-	-	-	-	-
118	295/75R22.5	REGIONAL S12	9.00	14	144/141M	-	2800	760	2575	760	1014	298	14.5	YES	-	-	-	-	-	-	-
119	295/75R22.5	REGIONAL S12	9.00	16	146/143M	-	3000	830	2725	830	1014	298	14.5	YES	-	-	-	-	-	-	-
120	295/75R22.5	REGIONAL T12	9.00	14	144/141M	-	2800	760	2575	760	1014	298	10.75	YES	-	-	-	-	-	-	-

No.	Size	HT Pattern	Rim	Ply Rating	LI/SS	Second LI/SS	Max. Load (Single-KG)	Max. Pressure (Single-KPa)	Max. Load (Dual-KG)	Max. Pressure (Dual-KPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	DOT	M+S	3PMSF	EU-RR (Level)	EU-WG (Level)	EU-N (Level)	EU-N (dB)	HL
121	295/75R22.5	REGIONAL T12	9.00	16	146/143M	-	3000	830	2725	830	1014	298	10.75	YES	-	-	-	-	-	-	-
122	295/75R22.5	WINTER G11	9.00	16	146/143M	-	3000	830	2725	830	1026	298	15.0	YES	-	-	-	-	-	-	-
123	295/80R22.5	HIGHWAY D11	9.00	16	152/148M	-	3550	850	3150	850	1044	298	16.0	YES	YES	YES	C	C	2	75	-
124	295/80R22.5	HIGHWAY S11	9.00	16	152/148M	-	3550	850	3150	850	1044	298	14.0	YES	YES	YES	D	C	2	73	-
125	295/80R22.5	HIGHWAY S11	9.00	18	154/149M	-	3750	850	3250	850	1044	298	14.0	YES	YES	YES	D	C	2	73	HL
126	295/80R22.5	MIXED G15	9.00	16	152/148K	-	3550	850	3150	850	1044	298	19.0	YES	YES	YES	D	B	2	73	-
127	295/80R22.5	REGIONAL D11	9.00	16	152/148M	-	3550	850	3150	850	1044	298	20.5	YES	YES	YES	E	B	2	75	-
128	295/80R22.5	REGIONAL S11	9.00	16	152/148M	-	3550	850	3150	850	1044	298	16.5	YES	YES	YES	C	C	2	73	-
129	295/80R22.5	REGIONAL S11	9.00	18	154/149M	-	3750	850	3250	850	1044	298	16.5	YES	YES	YES	C	C	2	73	HL
130	295/80R22.5	URBAN G12	9.00	16	152/148M	-	3550	850	3150	850	1044	298	17.0	YES	YES	-	D	B	1	70	-
131	295/80R22.5	URBAN G12	9.00	18	152/149M	-	3550	900	3250	900	1050	298	17.0	YES	-	-	-	-	-	-	-
132	295/80R22.5	URBAN G12	9.00	18	154/149M	-	3750	850	3250	850	1044	298	17.0	YES	YES	-	D	B	1	70	HL
133	295/80R22.5	URBAN G15	9.00	18	152/149J	-	3550	900	3250	900	1056	298	20.0	YES	-	-	-	-	-	-	-
134	295/80R22.5	WINTER D11	9.00	16	152/148M	-	3550	850	3150	850	1044	298	20.5	YES	YES	YES	D	B	2	74	-
135	295/80R22.5	WINTER D15	9.00	16	152/148K	-	3550	850	3150	850	1044	298	20.0	YES	YES	YES	D	C	2	73	-
136	295/80R22.5	WINTER D15	9.00	18	152/149K	-	3550	900	3250	900	1056	298	20.0	YES	-	-	-	-	-	-	-
137	295/80R22.5	WINTER G11	9.00	18	152/149K	-	3550	900	3250	900	1050	298	15.0	YES	-	-	-	-	-	-	-
138	305/70R19.5	REGIONAL D12	9.00 (8.25)	18	148/145M	-	3150	850	2900	850	923	305	16.0	YES	YES	YES	D	C	2	73	-
139	305/70R19.5	REGIONAL S15	9.00 (8.25)	18	148/145M	-	3150	850	2900	850	923	305	13.5	YES	YES	YES	D	B	2	73	-
140	305/70R22.5	URBAN G15	9.00	16	152/148J	154/150E	3550	900	3150	900	1000	305	20.0	YES	-	-	-	-	-	-	-
141	315/60R22.5	HIGHWAY D11	9.75	16	152/148L	-	3550	900	3150	900	950	313	16.5	YES	YES	YES	C	C	2	75	-
142	315/60R22.5	HIGHWAY S11	9.75	16	152/148L	-	3550	900	3150	900	950	313	14.5	YES	YES	YES	D	C	2	73	-
143	315/60R22.5	HIGHWAY S11	9.75	18	154/150L	152/148M	3750	900	3350	900	950	313	14.5	YES	YES	YES	D	C	2	73	HL
144	315/60R22.5	REGIONAL D11	9.75	16	152/148L	-	3550	900	3150	900	950	313	19.5	YES	YES	YES	E	B	2	75	-
145	315/60R22.5	REGIONAL S11	9.75	16	152/148L	-	3550	900	3150	900	950	313	14.5	YES	YES	YES	C	C	2	73	-
146	315/60R22.5	REGIONAL S11	9.75	18	154/150L	152/148M	3750	900	3350	900	950	313	14.5	YES	YES	YES	C	C	2	73	HL
147	315/70R22.5	HIGHWAY D11	9.00	16	154/150L	152/148M	3750	900	3350	900	1014	312	16.5	YES	YES	YES	C	C	2	75	-
148	315/70R22.5	HIGHWAY D11	9.00	18	156/150L	154/150M	4000	900	3350	900	1014	312	16.5	YES	YES	YES	C	C	2	75	HL
149	315/70R22.5	HIGHWAY S11	9.00	16	154/150L	152/148M	3750	900	3350	900	1014	312	15.0	YES	YES	YES	D	C	2	73	-
150	315/70R22.5	HIGHWAY S11	9.00	18	156/150L	154/150M	4000	900	3350	900	1014	312	15.0	YES	YES	YES	D	C	2	73	HL
151	315/70R22.5	REGIONAL D11	9.00	16	154/150L	152/148M	3750	900	3350	900	1014	312	20.0	YES	YES	YES	E	B	2	75	-
152	315/70R22.5	REGIONAL D11	9.00	18	156/150L	154/150M	4000	900	3350	900	1014	312	20.0	YES	YES	YES	E	B	2	75	HL
153	315/70R22.5	REGIONAL S11	9.00	16	154/150L	152/148M	3750	900	3350	900	1014	312	15.5	YES	YES	YES	C	C	2	73	-
154	315/70R22.5	REGIONAL S11	9.00	18	156/150L	154/150M	4000	900	3350	900	1014	312	15.5	YES	YES	YES	C	C	2	73	HL
155	315/70R22.5	WINTER D11	9.00	16	154/150L	152/148M	3750	900	3350	900	1014	312	20.0	YES	YES	YES	D	B	2	74	-
156	315/70R22.5	WINTER D11	9.00	18	156/150L	154/150M	4000	900	3350	900	1014	312	20.0	YES	YES	YES	D	B	2	74	HL
157	315/70R22.5	WINTER D15	9.00	16	154/150L	-	3750	900	3350	900	1014	312	20.0	YES	YES	YES	D	C	2	73	-
158	315/80R22.5	HIGHWAY D11	9.00	18	154/150M	-	3750	825	3350	825	1076	312	17.0	YES	YES	YES	C	C	2	75	-
159	315/80R22.5	HIGHWAY D11	9.00	20	156/150L	154/150M	4000	850	3350	850	1076	312	17.0	YES	YES	YES	C	C	2	75	-
160	315/80R22.5	HIGHWAY S11	9.00	18	154/150M	-	3750	825	3350	825	1076	312	15.0	YES	YES	YES	D	C	2	73	-

No.	Size	HT Pattern	Rim	Ply Rating	LI/SS	Second LI/SS	Max. Load (Single-KG)	Max. Pressure (Single-KPa)	Max. Load (Dual-KG)	Max. Pressure (Dual-KPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	DOT	M+S	3PMSF	EU-RR (Level)	EU-WG (Level)	EU-N (Level)	EU-N (dB)	HL
161	315/80R22.5	HIGHWAY S11	9.00	20	156/150L	154/150M	4000	850	3350	850	1076	312	15.0	YES	YES	YES	D	C	2	73	-
162	315/80R22.5	HIGHWAY S11	9.00	22	158/150L	154/150M	4250	900	3350	900	1076	312	15.0	YES	YES	YES	D	C	2	73	HL
163	315/80R22.5	MIXED D11	9.00	20	156/150K	-	4000	850	3350	850	1076	312	21.0	YES	YES	YES	D	B	2	73	-
164	315/80R22.5	MIXED G11	9.00	18	154/150M	-	3750	825	3350	825	1076	312	17.0	YES	YES	YES	D	B	2	73	-
165	315/80R22.5	MIXED G11	9.00	20	156/150L	-	4000	850	3350	850	1076	312	17.0	YES	YES	YES	D	B	2	73	-
166	315/80R22.5	MIXED G11	9.00	20	157/154K	-	4125	900	3750	900	1076	312	17.0	YES	-	-	-	-	-	-	-
167	315/80R22.5	MIXED G15	9.00	20	156/150K	-	4000	850	3350	850	1076	312	19.0	YES	YES	YES	D	B	2	73	-
168	315/80R22.5	MIXED G15	9.00	22	158/150K	-	4250	900	3350	900	1076	312	19.0	YES	YES	YES	D	B	2	73	-
169	315/80R22.5	REGIONAL D11	9.00	18	154/150M	-	3750	825	3350	825	1076	312	22.0	YES	YES	YES	E	B	2	75	-
170	315/80R22.5	REGIONAL D11	9.00	20	156/150L	154/150M	4000	850	3350	850	1076	312	22.0	YES	YES	YES	E	B	2	75	-
171	315/80R22.5	REGIONAL S11	9.00	20	156/150L	154/150M	4000	850	3350	850	1076	312	15.5	YES	YES	YES	C	C	2	73	-
172	315/80R22.5	REGIONAL S11	9.00	22	158/150L	154/150M	4250	900	3350	900	1076	312	15.5	YES	YES	YES	C	C	2	73	HL
173	315/80R22.5	WINTER D11	9.00	18	154/150M	-	3750	825	3350	825	1076	312	22.0	YES	YES	YES	D	B	2	74	-
174	315/80R22.5	WINTER D11	9.00	20	156/150L	154/150M	4000	900	3350	900	1076	312	22.0	YES	YES	YES	D	B	2	74	-
175	315/80R22.5	WINTER D15	9.00	18	154/150K	-	3750	825	3350	825	1082	312	20.0	YES	-	-	-	-	-	-	-
176	315/80R22.5	WINTER D15	9.00	18	154/150M	-	3750	825	3350	825	1076	312	20.0	YES	YES	YES	D	C	2	73	-
177	315/80R22.5	WINTER D15	9.00	18	154/151K	-	3750	830	3450	830	1082	312	20.0	YES	-	-	-	-	-	-	-
178	315/80R22.5	WINTER D15	9.00	20	156/150K	-	4000	850	3350	850	1082	312	20.0	YES	-	-	-	-	-	-	-
179	315/80R22.5	WINTER D15	9.00	20	156/150L	-	4000	850	3350	850	1076	312	20.0	YES	YES	YES	D	C	2	73	-
180	315/80R22.5	WINTER D15	9.00	20	157/154K	-	4125	900	3750	900	1082	312	20.0	YES	-	-	-	-	-	-	-
181	315/80R22.5	WINTER G11	9.00	18	154/151K	-	3750	830	3450	830	1076	312	15.0	YES	-	-	-	-	-	-	-
182	385/55R19.5	HIGHWAY T11	12.25	18	156J	-	4000	900	-	-	919	386	12.5	YES	YES	-	C	C	2	73	-
183	385/55R22.5	HIGHWAY S11	12.25	18	158L	-	4250	850	-	-	996	386	12.0	YES	YES	YES	D	C	2	73	-
184	385/55R22.5	HIGHWAY S11	12.25	20	160K	158L	4500	900	-	-	996	386	12.0	YES	YES	YES	D	C	2	73	-
185	385/55R22.5	HIGHWAY T11	12.25	18	158L	-	4250	850	-	-	996	386	12.0	YES	YES	-	C	C	2	73	-
186	385/55R22.5	HIGHWAY T11	12.25	20	160K	158L	4500	900	-	-	996	386	12.0	YES	YES	-	C	C	2	73	-
187	385/55R22.5	MIXED T11	12.25	18	158L	-	4250	850	-	-	996	386	16.5	YES	YES	YES	D	B	2	73	-
188	385/55R22.5	MIXED T11	12.25	20	160J	-	4500	900	-	-	996	386	16.5	YES	YES	YES	D	B	2	73	-
189	385/55R22.5	REGIONAL S11	12.25	18	158L	-	4250	850	-	-	996	386	13.5	YES	YES	YES	C	C	2	73	-
190	385/55R22.5	REGIONAL S11	12.25	20	160K	158L	4500	900	-	-	996	386	13.5	YES	YES	YES	C	C	2	73	-
191	385/55R22.5	WINTER T11	12.25	18	158L	-	4250	850	-	-	996	386	14.5	YES	YES	YES	D	A	2	72	-
192	385/55R22.5	WINTER T11	12.25	20	160K	158L	4500	900	-	-	996	386	14.5	YES	YES	YES	D	A	2	72	-
193	385/65R22.5	HIGHWAY T11	11.75	20	160K	158L	4500	900	-	-	1072	389	13.5	YES	YES	-	C	C	2	73	-
194	385/65R22.5	HIGHWAY T11	11.75	24	164K	158L	5000	900	-	-	1072	389	13.5	YES	YES	-	C	C	2	73	HL
195	385/65R22.5	MIXED G12	11.75	18	158L	-	4250	850	-	-	1072	389	18.0	YES	YES	-	D	C	2	73	-
196	385/65R22.5	MIXED G12	11.75	20	160K	158L	4500	900	-	-	1072	389	18.0	YES	YES	-	D	C	2	73	-
197	385/65R22.5	MIXED G12	11.75	24	164J	-	5000	900	-	-	1072	389	18.0	YES	YES	-	D	C	2	73	-
198	385/65R22.5	MIXED T11	11.75	18	158K	-	4250	850	-	-	1072	389	16.5	YES	YES	YES	D	B	2	73	-
199	385/65R22.5	MIXED T11	11.75	20	160K	-	4500	900	-	-	1072	389	16.5	YES	YES	YES	D	B	2	73	-
200	385/65R22.5	MIXED T11	11.75	24	164J	-	5000	900	-	-	1072	389	16.5	YES	YES	YES	D	B	2	73	-

No.	Size	HT Pattern	Rim	Ply Rating	LI/SS	Second LI/SS	Max. Load (Single-KG)	Max. Pressure (Single-KPa)	Max. Load (Dual-KG)	Max. Pressure (Dual-KPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	DOT	M+S	3PMSF	EU-RR (Level)	EU-WG (Level)	EU-N (Level)	EU-N (dB)	HL
201	385/65R22.5	REGIONAL G15	11.75	18	158K	-	4250	850	-	-	1072	389	16.5	YES	YES	-	D	C	2	73	-
202	385/65R22.5	REGIONAL G15	11.75	18	158K	-	4250	830	-	-	1072	389	16.5	YES	-	-	-	-	-	-	-
203	385/65R22.5	REGIONAL G15	11.75	20	160J	-	4500	900	-	-	1072	389	16.5	YES	YES	-	D	C	2	73	-
204	385/65R22.5	REGIONAL G15	11.75	20	160J	-	4500	900	-	-	1072	389	16.5	YES	-	-	-	-	-	-	-
205	385/65R22.5	REGIONAL G15	11.75	24	164J	-	5000	900	-	-	1072	389	16.5	YES	YES	-	D	C	2	73	-
206	385/65R22.5	REGIONAL S11	11.75	20	160K	158L	4500	900	-	-	1072	389	15.5	YES	YES	YES	C	C	2	73	-
207	385/65R22.5	REGIONAL S11	11.75	24	164K	158L	5000	900	-	-	1072	389	15.5	YES	YES	YES	C	C	2	73	HL
208	385/65R22.5	REGIONAL S16	11.75	20	160J	-	4500	900	-	-	1072	389	13.0	YES	YES	-	D	C	2	73	-
209	385/65R22.5	REGIONAL S16	11.75	20	160K	158L	4500	900	-	-	1072	389	13.0	YES	YES	-	D	C	2	73	-
210	385/65R22.5	REGIONAL S16	11.75	24	164J	-	5000	900	-	-	1072	389	13.0	YES	YES	-	D	C	2	73	-
211	385/65R22.5	WINTER G11	11.75	20	160J	-	4500	900	-	-	1072	389	16.5	YES	-	-	-	-	-	-	-
212	385/65R22.5	WINTER T11	11.75	20	160K	158L	4500	900	-	-	1072	389	15.5	YES	YES	YES	D	A	2	72	-
213	385/65R22.5	WINTER T11	11.75	24	164K	158L	5000	900	-	-	1072	389	15.5	YES	YES	YES	D	A	2	72	HL
214	425/65R22.5	HIGHWAY T11	12.25	20	165K	-	5150	825	-	-	1124	422	14.5	YES	YES	-	C	C	2	73	-
215	425/65R22.5	MIXED G12	12.25	20	165K	-	5150	825	-	-	1124	430	18.5	YES	YES	-	D	C	2	73	-
216	425/65R22.5	MIXED G15	12.25	20	165K	-	5150	825	-	-	1124	430	18.5	YES	YES	YES	D	B	2	73	-
217	425/65R22.5	MIXED T11	12.25	20	165J	-	5150	825	-	-	1124	430	17.5	YES	YES	YES	D	B	2	73	-
218	425/65R22.5	MIXED T11	12.25	20	165K	-	5150	830	-	-	1124	422	17.5	YES	YES	YES	D	B	2	73	-
219	425/65R22.5	REGIONAL G12	12.25	18	162K	-	4750	760	-	-	1124	422	17.5	YES	-	-	-	-	-	-	-
220	425/65R22.5	REGIONAL G12	12.25	20	165J	-	5150	825	-	-	1124	430	17.5	YES	YES	-	D	B	2	73	-
221	425/65R22.5	REGIONAL G12	12.25	20	165J	-	5150	830	-	-	1124	422	17.5	YES	-	-	-	-	-	-	-
222	435/50R19.5	HIGHWAY T11	14.00	18	156J	-	4000	850	-	-	931	438	12.5	YES	YES	-	C	C	2	73	-
223	435/50R19.5	HIGHWAY T11	14.00	20	160J	-	4500	900	-	-	931	438	12.5	YES	YES	-	C	C	2	73	-
224	445/45R19.5	HIGHWAY T11	15.00	18	156J	-	4000	900	-	-	895	446	12.5	YES	YES	-	C	C	2	73	-
225	445/45R19.5	HIGHWAY T11	15.00	20	160J	-	4500	900	-	-	895	446	12.5	YES	YES	-	C	C	2	73	-
226	445/50R22.5	HIGHWAY D15	14.00	18	155L	-	3875	700	-	-	1024	445	20	YES	-	-	-	-	-	-	-
227	445/50R22.5	HIGHWAY D15	14.00	18	158L	-	4250	760	-	-	1024	445	20	YES	-	-	-	-	-	-	-
228	445/50R22.5	HIGHWAY D15	14.00	20	161L	-	4625	830	-	-	1024	445	20	YES	-	-	-	-	-	-	-
229	445/50R22.5	HIGHWAY D15	14.00	20	161L	-	4625	850	-	-	1024	445	20	YES	-	-	-	-	-	-	-
230	445/50R22.5	HIGHWAY T12	14.00	20	155L	-	3875	700	-	-	1018	445	10.5	YES	-	-	-	-	-	-	-
231	445/50R22.5	HIGHWAY T12	14.00	20	158L	-	4250	760	-	-	1018	445	10.5	YES	-	-	-	-	-	-	-
232	445/50R22.5	HIGHWAY T12	14.00	20	161L	-	4625	830	-	-	1018	445	10.5	YES	-	-	-	-	-	-	-
233	445/50R22.5	HIGHWAY T12	14.00	20	161L	-	4625	850	-	-	1018	445	10.5	YES	-	-	-	-	-	-	-
234	445/65R22.5	MIXED G15	13.00	20	169J/K	-	5800	900	-	-	1150	454	18.5	YES	YES	YES	D	B	2	73	-
235	445/65R22.5	MIXED T11	13.00	20	168K	-	5600	830	-	-	1150	444	18.0	YES	YES	YES	D	B	2	73	-
236	445/65R22.5	MIXED T11	13.00	20	169J/K	-	5800	900	-	-	1150	454	18.0	YES	YES	YES	D	B	2	73	-